# MATERIAL SAFETY DATA SHEET

TERMIN-8 WOOD PRESV., GREEN

PRODUCT NAME: TERMIN-8 WOOD PRESV., GREEN HMIS CODES: HFRP

**PROCUCT CODE:** 0900-0903

1\*2 0 C

Page:

======= SECTION I - MANUFACTURER IDENTIFICATION =================================

JASCO Chemical Corp. MANUFACTURER'S NAME :

1008 N. Fuller St. ADDRESS

Santa Ana, CA. 92701

**EMERGENCY PHONE** : 5/03 : 800-424-9300 DATE PRINTED INFORMATION PHONE (714) 547-6951 NAME OF PREPARER : COM

====== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ==========

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP		WEIGHT PERCENT
ALIPHATIC PETROLEUM DISTILLATES  OSHA PEL: 400 PPM, ACGIH TLV: 100 PPM, OTHER: N/A	64742-96-7	2	68	30
COPPER NAPHTHENATE 8%; COPPER 8% FUNGICIDE  OSHA PEL: UNKNOWN, ACGIH TLV: UNKNOWN, OTHER: 1 mg/m3 Cu	1338-02-9	1	77	25

\*\*\* No toxic chemical (s) subject to the reporting requirements of section 313 of Title III of 40 CFR 372 are present. \*\*\* JASCO TERMIN-8 CONFORMS TO FEDERAL SPECIFICATION TT-W-572, TYPE II, COMPOSITION "C", EQUIVALENT TO METALLIC COPPER 2%.

======== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =================

**BOILING RANGE:** 310 DEG. F SPECIFIC GRAVITY (H2O=1): 0.87

VAPOR DENSITY: HEAVIER THAN AIR **EVAPORATION RATE:** SLOWER THAN ETHER

COATING V.O.C.: 342.0 g/L

SOLUBILITY IN WATER: NEGLIGIBLE

**APPEARANCE AND ODOR:** GREEN LIQUID; HYDROCARBON ODOR.

========= SECTION IV - FIRE AND EXPLOSION HAZARD DATA ==========================

**METHOD USED: TOC FLASH POINT:** 104 DEG. F

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1 **UPPER:** 6

**EXTINGUISHING MEDIA:** FOAM, CO2, DRY CHEMICAL

# SPECIAL FIREFIGHTING PROCEDURES

FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING WHEN FIGHTING FIRES.

# UNUSUAL FIRE AND EXPLOSION HAZARDS

EXPOSURE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS. COOL CONTAINERS WITH WATER SPRAY.

**STABILITY: STABLE CONDITIONS TO AVOID** 

HEAT, SPARKS AND OPEN FLAMES.

## **INCOMPATIBILITY (MATERIALS TO AVOID)**

STRONG OXIDANTS, STONG ACIDS AND BASES.

# MATERIAL SAFETY DATA SHEET

**TERMIN-8 WOOD PRESV., GREEN** 

# HAZARDOUS DECOMPOSITION OR BYPRODUCTS

BURNING MAY PRODUCE CARBON MONOXIDE OR COPPER FUME.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

#### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

MAY CAUSE HEADACHE, INCOORDINATION.

## SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN AND EYE IRRITANT.

## SKIN ABSORPRTION HEALTH RISKS AND SYMPTONS OF EXPOSURE

MAY CAUSE ITCHING, DRYNESS.

#### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CAUSES GASTROINTESTINAL TRACT IRRITATION, VOMITING, DEPRESSION.

# **HEALTH HAZARDS (ACUTE AND CHRONIC)**

HARMFUL OR FATAL IF SWALLOWED. ASPIRATION INTO LUNGS MAY CAUSE CHEMICAL PNEUMONITIS. UNCONCIOUSNESS IF INHALED IN LARGE DOSES.

# CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

THIS PRODUCT IS NOT LISTED IN THE NTP, IARC OR OSHA LISTS FOR CARCINOGENICITY.

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

SOME SKIN CONDITIONS MAY BE AGGRAVATED.

### **EMERGENCY AND FIRST AID PROCEDURES**

SKIN: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. INGESTION: DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.

======= SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ====================

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

EXTINGUISH ALL SOURCES OF IGNITION. CONTAIN AND ABSORB WITH SAND OR VERMICULITE. DO NOT LET INTO SEWERS OR WATER SOURCES.

## WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE IN A COOL, VENTILATED AREA. KEEP AWAY FROM SPARKS AND OPEN FLAMES. KEEP CONTAINER CLOSED WHEN NOT IS USE.

# OTHER PRECAUTIONS

GROUND CONTAINERS WHEN FILLING OR EMPTYING.

Page: 2

# MATERIAL SAFETY DATA SHEET TERMIN-8 WOOD PRESV., GREEN Page: 3 REPIRATORY PROTECTION NIOSH-APPROVED RESPIRATOR IF TLV IS EXCEEDED. **VENTILATION** BOTH LOCAL AND MECHANICAL EXHAUSTS ARE RECOMMENDED. PROTECTIVE GLOVES SOLVENT RESISTANT SUCH AS NEOPRENE. **EYE PROTECTION** SAFETY GLASSES/GOGGLES. OTHER PROTECTIVE CLOTHING OR EQUIPMENT SAFETY SHOWER/EYEWASH. WORK/HYGIENIC PRACTICES DO NOT EAT, DRINK OR SMOKE AROUND PRODUCT. WASH HANDS AFTER USE.

THIS INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF ACCURATE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION OR

# SHIPPING INFORMATION

DOT PROPER SHIPPING NAME;
CLEANING COMPOUNDS - NON REGULATED MATERIAL

GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS.